







1 MAIN FRAME(WELDED)  
MATERIAL THICKNESS 1.5 AND 2 mm  
2 ea.

2 MOUNTIN RAILS  
MATERIAL THICKNESS 2 mm  
4 ea.

3 FRONT DOOR  
%80 PERFORATED  
MATERIAL THICKNESS 1.2 mm  
1 ea.  
SINGLE POINT HANDELOCK

4 CLOSED PROFILE DEPTH SUPPORT  
MATERIAL THICKNESS 1.5 mm  
4 ea.

5 REAR DOORS(LEFT / RIGHT)  
%80 PERFORATED  
MATERIAL THICKNESS 1.2 mm  
HANDLE LOCK  
WITH 3 POINT LOCKING MECH

6 TOP PANEL / REINFORECD WITH WELDED PROFILES  
MATERIAL THICKNESS 0.8 mm  
1 ea.

7 CASTOR HEAVY DUTY  
4 ea.

10 PDU MOUNTING BRACKET  
MATERIAL THICKNESS 1.5 mm  
4 ea.

12 SIDE PANEL  
MATERIAL THICKNESS 0.8 mm  
8 ea.  
"O" LOCK

8 LEVELING FEET  
4 ea.

11 GROUNDING KIT  
3 ea.

9 BYING KIT  
4 ea.  
2 REAR  
2 FRONT

LN-SRDC-42U8012-SV-CC-DGAA  
LN-SRDC-42U8012-SV-CC-DG00\*\*

PRODUCT CODE

LN-SRDC-42U8012-SV-CC-DGAA

LN-SRDC-42U8012-SV-CC-DG00

